



L.P.S. KENBEC INC
1368 MONTÉE MASSON
LAVAL, QC H7E 4P2
TEL:(450)-661-0411 / (877) 661-0411
FAX : (450)-661-0471
info@lpskenbec.com



Grease dispensing Pump 50:1 Ratio



RECOMMENDED FOR:
GREASE UP TO NLGI #2

**Part # 1220R
Series**

To fit 120 pounds/54kg drums



Air operated pump for short/long distance grease distribution, for high pressure greasing. Ideal for dispensing medium/high viscosity grease. Suitable for mobile installations and centralised fixed systems.

FEATURES

- Heavy duty 50:1
- Free flow rate 1500g per minute @ 90 PSI
- Maximum air pressure 110 PSI
- Air consumption 4.59 CFM @ 100 PSI
- Pump tube 1 3/16" diameter and 29" long
- Pump head 2 1/2" diameter and 10" long
- Suction tube constructed with no seals to eliminate excessive wear

APPLICATION

- Automotive
- Industrial
- Agriculture



Control Handle # 1536A




"Z" Swivel # 1545



Filter & Regulator unit
1559A-ASSY



Drum Cover # 65385



Follower Plate # 1524



Drum Dolly # 120-S



Drum Dolly # 147



High pressure grease hoses

Part #	Cover	Follower Plate	Control Handle	"Z" swivel	Hose Length	Drum Dolly Part #	Filter & Regulator
1220R	included	included	none	none	none	none	Optional
1220R-00	included	included	included	included	none	147	Optional
1220R-06	included	included	included	included	¼" x 6'	120-S	Optional
1220R-10	included	included	included	included	¼" x 10'	147	Optional
1220R-12	included	included	included	included	¼" x 12'	147	Optional
1220R-16	included	included	included	included	¼" x 16'	147	Optional
1220R-20	included	included	included	included	¼" x 20'	147	Optional
1220R-25	included	included	included	included	¼" x 25'	147	Optional
1220RAR	none	none	none	none	none	none	Optional