



L.P.S. KENBEC INC

1368 MONTÉE MASSON
LAVAL, QC H7E 4P2
TEL: (450)-661-0411 / (877) 661-0411
FAX : (450)-661-0471
info@lpskenbec.com



Oil Drain

Part #1234

**Waste Oil Drain
80 Litres**



FEATURES

- ❖ Adjustable waste oil drain with minimum height 53 inches and maximum height 65 inches
- ❖ 80 Litres wheel mounted tank with front and rear ball bearing wheels (3" front casters and 6" rear wheels)
- ❖ Centrally mounted bowl on swivel joint for positioning
- ❖ Maximum collection capacity without draining is 60L
- ❖ 14 inch diameter funnel
- ❖ 15L capacity collection bowl with adjustable height
- ❖ 6.5 foot long drain hose
- ❖ 7 PSI maximum draining air pressure
- ❖ Level sight gauge: scale in litres and gallons
- ❖ Anti-splash screen/filter provides useful support for draining used filters
- ❖ Removable steel tool tray 6" x 8" x 2"

APPLICATIONS

- For gravity drain of fluids from engines, gearboxes or differentials of all motor vehicles placed on an auto-lift or pit.

SELF EVACUATING:

FOLLOW THIS SIMPLE PROCEDURE

- 1) Close all valves and raise funnel tubes up until it snaps
- 2) Apply air to the tank
- 3) Once the tank has pressurized, roll the tank to where you want to discharge the old oil
- 4) Place drain tube in waste oil container
- 5) Open the valve at the opposite end of the drain hose

